

## VL120005

Bestellnummer: VL120005

Bruttopreis (EVP): CHF **538.40**

### Audio amplifier 2x50W

Digitaler Verstärker mit 3 Eingängen. Mit 2x50W@8 Ohm als Standardausgang kann er durch Brückenschaltung auch auf 1x100W@4 Ohm umgeschaltet werden.

#### Die Bedienungsanleitung finden Sie

Digitaler Verstärker mit 3 Eingängen. Mit 2x50W@8 Ohm als Standardausgang kann er durch Brückenschaltung auch auf 1x100W@4 Ohm umgeschaltet werden.

#### Die Bedienungsanleitung finden Sie

### Empfohlenes Zubehör

MC-415S/SW-CH	Ecolor Steckdosenleiste, Schwarz mit Schalter
PRORCARCA2	2 X RCA - 2 X RCA M-M 2 M
PRORCARCA5	2 X RCA - 2 X RCA M-M 5 M



Audio Input	2 stereo (L+R RCA, 3.5mm jack) 1 10K Ω 1 digital audio (SPDIF, fiber connector)
Audio Output	1 amplifier (4P captive screw connector) stereo loop out (3.5mm jack)
Output Type	constant resistance 4Ω/8Ω
Power Output	2x50W / 1x100W (bridge)
Voltage Gain	±26dB
Frequency Response	20Hz-20KHz
CMRR	>80dB@20Hz to 20KHz
SNR	85dB(Max)
Stereo Channel Separation	>80dB@20Hz to 20KHz
Bandwidth	20Hz-25KHz
THD+Noise	<0.01% @1KHz
Control	Button, RS232, TCP/IP, optional IR remote
Power Supply	DC33V, 4A
Chassis	W148xH44xD160mm
Dimension	